

ARTIGIANO™

GLAZED CERAMIC

Enjoy the Charm of Handcrafted Style

- ARTISAN APPEAL
 - Captures the warmth and charm of old-world Europe
 - Hand-painted look and irregular edges reflect the beauty and tradition of handmade tile
 - Enjoy a handcrafted, artisan look
- CREATE SUBTLE FEATURE WALLS
 - Offered in two linear sizes, ideal for creating backsplashes: 3 x 6 and 3 x 12
 - Neutral, earthy color palette easily coordinates with virtually any room design

3 x 12 WALL TILE



ITALIAN ALPS AR93



TREMITI SAND AR94



RIVIERA POMPEII AR95



VENICE STATUE AR96



MILAN ARENA AR97



ROMAN SKYLINE AR98



FLORENTINE GATES AR99

3 x 6 WALL TILE



ITALIAN ALPS AR93



TREMITI SAND AR94



RIVIERA POMPEII AR95



VENICE STATUE AR96



MILAN ARENA AR97



ROMAN SKYLINE AR98



FLORENTINE GATES AR99

USAGE

| Floors | Walls | Countertops |
|--------|-------|-------------|
| | | |


IMAGINE WHAT'S POSSIBLE™





Photo features Artigiano™ Riviera Pompeii and Italian Alps 3 x 6 on the wall.

SIZES

| | | | Thickness | Sq. Ft./ Carton | Pieces/ Carton |
|---|---------------------|--|-----------|--------------------|-------------------|
|  | 3 x 12 Wall Tile | (2-15/16" x 11-3/4") (7.50 cm x 30.00 cm) | 5/16" | 5.28 | 22 |
|  | 3 x 6 Wall Tile | (2-15/16" x 5-7/8") (7.50 cm x 15.00 cm) | 5/16" | 5.28 | 44 |

TRIM

| Type | Number | Size | Pieces/ Carton |
|--|--------|-------|-------------------|
|  Bullnose (6" Side) | S-4369 | 3 x 6 | 44 |

INSTALLATION

| Grout Joint Recommendation | Shade Variation |
|----------------------------|--|
| 1/8" |  Low (V1) |

APPLICATIONS

| | Target DCOF Wet | Suitable |
|--|--------------------|----------|
| Dry & Level – Interior Floor | N/A | |
| Wet & Level – Interior Floor | ≥ 0.42 | |
| Shower Floors (Residential or Light Commercial) | ≥ 0.42 | |
| Exterior Floor Applications (including pool decking & other wet areas with minimal footwear) | ≥ 0.60 | |
| Ramps & Inclines | ≥ 0.65 | |
| Walls/Backsplashes | N/A | ✓ |
| Countertops | N/A | |
| Pool Linings | N/A | |

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

| | ASTM# | Result |
|---------------------|-------|-------------|
| Water Absorption | C373 | < 20.0% |
| Breaking Strength | C648 | 120-230 lbs |
| Scratch Hardness | MOHS | 4.0-6.0 |
| Chemical Resistance | C650 | Resistant |
| Abrasion Resistance | C1027 | N/A |

See page 488 for additional information on Test Results and Classifications.

See "Factors to Consider" and "Important Product Warranty Information" on pages 492-493.